

---

# **error-tracker Documentation**

***Release 1.0***

**Sonu Kumar**

**Dec 01, 2019**



---

## Contents

---

<b>1</b>	<b>Features</b>	<b>3</b>
1.1	Quick start . . . . .	4
<b>2</b>	<b>Installation</b>	<b>5</b>
<b>3</b>	<b>Recording exception/error</b>	<b>7</b>
<b>4</b>	<b>Flask App setup</b>	<b>9</b>
<b>5</b>	<b>Django App Setup</b>	<b>11</b>
<b>6</b>	<b>Using With Python App (NO WEB SERVER)</b>	<b>13</b>
6.1	Flask App Usage . . . . .	13
6.2	Django App Settings . . . . .	15
6.3	Notification notify feature . . . . .	17
6.4	Ticketing . . . . .	17
6.5	Masking Rule . . . . .	18
6.6	Custom Context Builder . . . . .	19
6.7	Using Mongo or other data store . . . . .	19



Error Tracker is a python app plugins for Flask and Django, that provides many of the essentials features of system exceptions tracking.



# CHAPTER 1

## Features

- Mask all the variables, including dict keys, HTTP request body which contain *password* and *secret* in their name.
- Recorded exceptions will be visible to the configured path
- Send notification on failures
- Record exceptions with frame data, including local and global variables
- Raise bugs or update ticket in Bug tracking systems.
- Provide customization for notification, context building, ticketing systems and more

### Exception Listing

#### Errors Seen

Host	Method	Path	Exception	Last seen	Occurrences	Action
http://127.0.0.1:5000/	GET	/go	IndentationError	2019-12-01 12:38:24.507043	1	Delete
http://127.0.0.1:5000/	GET	/go	RuntimeError	2019-12-01 12:38:11.642151	2	Delete
http://127.0.0.1:5000/	GET	/go	OSError	2019-12-01 12:37:45.876906	1	Delete
http://127.0.0.1:5000/	GET	/go	EOFError	2019-12-01 12:14:12.010774	1	Delete
http://127.0.0.1:5000/	GET	/go	KeyError	2019-11-30 10:46:08.704501	1	Delete
http://127.0.0.1:5000/	GET	/go	EnvironmentError	2019-11-30 10:46:04.704289	1	Delete
http://127.0.0.1:5000/	GET	/go	TypeError	2019-11-30 10:45:27.187173	1	Delete
http://127.0.0.1:5000/	GET	/dev/error/	AttributeError	2019-11-29 12:09:37.567483	1	Delete
http://127.0.0.1:5000/	GET	/go	ChildProcessError	2019-11-29 12:09:15.298448	1	Delete

### Detailed Exception

```
File "/Users/sonu/Desktop/ps/venv/py3.7/lib/python3.7/site-packages/flask/app.py", line 1820, in handle_user_exception
e = EOFError()
exc_value = EOFError()
handler = None
tb = <traceback object at 0x10f67cf00>

File "/Users/sonu/Desktop/ps/venv/py3.7/lib/python3.7/site-packages/flask/_compat.py", line 39, in reraise
tb = <traceback object at 0x10f67cf00>
value = EOFError()

File "/Users/sonu/Desktop/ps/venv/py3.7/lib/python3.7/site-packages/flask/app.py", line 1951, in full_dispatch_request
rv = None

File "/Users/sonu/Desktop/ps/venv/py3.7/lib/python3.7/site-packages/flask/app.py", line 1935, in dispatch_request
req = <Request 'http://127.0.0.1:5000/go' [GET]>
rule = <Rule '/go' (HEAD, OPTIONS, GET) -> die>

File "/Users/sonu/Desktop/ps/error-tracker/examples/flask-sample/app.py", line 55, in die
exceptions = [<class 'KeyError'>, <class 'ArithmeticError'>, <class 'BaseException'>, <class 'IndentationError'>, <class 'IndexError'>, <class 'MemoryError'>, <class 'NameError'>,
<class 'NotImplementedError'>, <class 'ImportError'>, <class 'FloatingPointError'>, <class 'EOFError'>, <class 'OSError'>, <class 'AssertionError'>, <class 'AttributeError'>, <class
'GeneratorExit'>, <class 'Exception'>, <class 'OSError'>, <class 'ImportError'>, <class 'NotImplementedError'>, <class 'RuntimeError'>]
foo = {'password': '*****', 'secret': '*****'}
password = '*****'
```

## 1.1 Quick start



## CHAPTER 2

---

### Installation

---

To install Error Tracker, open an interactive shell and run:

```
pip install error-tracker
```

Error Tracker can be used with

- Standalone Python application
- Flask Application
- Django Application

Using **Error Tracker** as simple as plugging any other module.



---

### Recording exception/error

---

An error/exception can be recorded using decorator or function call.

- To record the error using decorator, decorate a function with `track_exception` or `auto_track_exception`
- Where as to record error using function call use `record_exception` function.

All the data will be stored in the configured data store and these data will be available at configure URL path.



## CHAPTER 4

---

### Flask App setup

---

An instance of `AppErrorTracker` needs to be created and have to be configured with the correct data. Monitoring feature can be configured either using object based configuration or app-based configuration, the only important thing here is we should have all the required key configs in the `app.config` otherwise it will fail.

For object based configuration add **settings.py**

```
...
APP_ERROR_SEND_NOTIFICATION = True
APP_ERROR_RECIPIENT_EMAIL = ('example@example.com',)
APP_ERROR_SUBJECT_PREFIX = "Server Error"
APP_ERROR_EMAIL_SENDER = 'user@example.com'
```

#### **app.py**

```
from flask import Flask
from flask_mail import Mail
import settings
from error_tracker import AppErrorTracker, NotificationMixin
from flask_sqlalchemy import SQLAlchemy
...
app = Flask(__name__)
app.config.from_object(settings)
db = SQLAlchemy(app)
class Notifier(Mail, NotificationMixin):
    def notify(self, request, exception,
               email_subject=None,
               email_body=None,
               from_email=None,
               recipient_list=None):
        message = Message(email_subject, recipient_list, email_body, sender=from_
↪email)
        self.send(message)
mailer = Notifier(app=app)
error_tracker = AppErrorTracker(app=app, db=db, notifier=mailer)
```

(continues on next page)

(continued from previous page)

```
....  
  
....  
# Record exception when 404 error code is raised  
@app.errorhandler(403)  
def error_403(e):  
    error_tracker.record_exception()  
    # any custom logic  
  
# Record error using decorator  
@app.errorhandler(500)  
@error_tracker.track_exception  
def error_500(e):  
    # some custom logic  
....
```

Here, app, db and notifier parameters are optional. Alternatively, you could use the `init_app()` method.

If you start this application and navigate to <http://localhost:5000/dev/error>, you should see an empty page.

---

## Django App Setup

---

We need to update settings.py file as

- Add app `error_tracker.DjangoErrorTracker` to installed apps list
- Add Middleware `error_tracker.django.middleware.ExceptionTrackerMiddleWare` for exception tracking<sup>1</sup>.
- Other configs related to notification
- Add URLs to the list of URL patterns

```
...
APP_ERROR_RECIPIENT_EMAIL = ('example@example.com',)
APP_ERROR_SUBJECT_PREFIX = "Server Error"
APP_ERROR_EMAIL_SENDER = 'user@example.com'

INSTALLED_APPS = [
    ...
    'error_tracker.DjangoErrorTracker'
]
MIDDLEWARE = [
    ...
    'error_tracker.django.middleware.ExceptionTrackerMiddleWare'
]
```

We need to add URLs to the urls.py so that we can browse the default pages provided by Error Tracker

```
from error_tracker.django import urls

urlpatterns = [
    ...
    url("dev/", include(urls)),
]
```

---

<sup>1</sup> This should be added at the end so that it can process exception 1st in the middleware call stack.





---

## Using With Python App (NO WEB SERVER)

---

Choose either of the preferred framework, flask or Django and configure the app as per their specifications. For example, if we want to use Flask then do

- **Flask App**
  - Create Flask App instance
  - Create Error Tracker app instance
  - DO NOT call run method of Flask app instance
  - To track exception call `error_tracker.record_exception` method
- **Django App**
  - Create Django App with settings and all configuration
  - Set environment variable **DJANGO\_SETTINGS\_MODULE**
  - call `django.setup()`
  - `from error_tracker.django.middleware import error_tracker`
  - To track exception do `error_tracker.record_exception(None, exception)`

## 6.1 Flask App Usage

### 6.1.1 Lazy initialization

Use `error_tracker.init_app` method to configure

```
error_tracker = AppErrorTracker()  
...  
error_tracker.init_app(app=app, db=db, notifier=notifier)
```

## 6.1.2 Config details

- **Enable or disable notification sending feature**

```
APP_ERROR_SEND_NOTIFICATION = False
```

- **Email recipient list**

```
APP_ERROR_RECIPIENT_EMAIL = None
```

- **Email subject prefix to be used by email sender**

```
APP_ERROR_SUBJECT_PREFIX = ""
```

- **Mask value with following string**

```
APP_ERROR_MASK_WITH = "*****"
```

- **Masking rule** App can mask all the variables whose lower case name contains one of the configured string .. code:

```
APP_ERROR_MASKED_KEY_HAS = ("password", "secret")
```

Above configuration will mask the variable names like

```
password
secret
PassWord
THis_Is_Secret
```

---

**Note:** Any variable names whose lower case string contains either *password* or *secret*

---

- **Browse link in your service app** List of exceptions can be seen at */dev/error*, but you can have other prefix as well due to some securities or other reasons.

```
APP_ERROR_URL_PREFIX = "/dev/error"
```

- **Email address used to construct Message object**

```
APP_ERROR_EMAIL_SENDER = "prod-issue@example.com"
```

## 6.1.3 Manual Exception Tracking

Error can be tracked programmatically using `AppErrorTracker`'s `record_exception` method.

```
error_tracker = AppErrorTracker(...)
...
try
    ...
catch Exception as e:
    error_tracker.record_exception()
```

Decorator based exception recording, record exception as it occurs in a method call.

---

**Note:** Exception will be re-raised so it must be caught in the caller or ignored.

---

```
error_tracker = AppErrorTracker(...)
@error_tracker.auto_track_exception
def fun():
    pass
```

## 6.2 Django App Settings

Error Tracker fits nicely with Django framework, error tracker can be configured in different ways. Multiple settings are available, these settings can be configured using settings file.

### 6.2.1 Setting details

- Home page list size, display 10 exceptions per page

```
EXCEPTION_APP_DEFAULT_LIST_SIZE = 10
```

- What all sensitive data should be masked

```
APP_ERROR_MASKED_KEY_HAS = ("password", "secret")
```

---

**Note:** This means any variables whose name have either password or secret would be masked

---

- Sensitive data masking value

```
APP_ERROR_MASK_WITH = '*****'
```

- Exception email subject prefix

```
APP_ERROR_SUBJECT_PREFIX = get('APP_ERROR_SUBJECT_PREFIX', '')
```

- Email sender's email id

```
APP_ERROR_EMAIL_SENDER = "server@example.com"
```

- Whom email should be sent in the case of failure

```
APP_ERROR_RECIPIENT_EMAIL = ('dev-group1@example.com', 'dev@example.com')
```

- By default only 500 errors are tracked but HTTP 404, 401 etc can be tracked as well

```
TRACK_ALL_EXCEPTIONS = True
```

---

**Note:** Below configurations are required path to some class.

---

- Custom Masking Module

```
APP_ERROR_MASKING_MODULE = "path to Masking class"
```

- Ticketing/Bugging module

```
APP_ERROR_TICKETING_MODULE = "path to Ticketing class"
```

---

**Note:** Class must not have any constructor arguments

---

- Notifier module

```
APP_ERROR_NOTIFICATION_MODULE = "path to Notification class"
```

---

**Note:** Class must not have any constructor arguments

---

- Context Builder module

```
APP_ERROR_CONTEXT_BUILDER_MODULE = "path to ContextBuilder class"
```

---

**Note:** Class must not have any constructor arguments

---

- Custom Model used for exceptions storage

```
APP_ERROR_DB_MODEL = "path to Model class"
```

---

**Note:** Class must implements all abstract methods

---

## 6.2.2 Manual Exception Tracking

Error can be tracked programmatically using ErrorTracker's object available in middleware module. For tracking exception call `error_tracker.record_exception` method.

```
from error_tracker.django.middleware import error_tracker

...
try
    ...
catch Exception as e:
    error_tracker.record_exception(request, e)
```

Decorator based exception recording, record exception as it occurs in a method call.

---

**Note:** Exception will be re-raised so it must be caught in the caller or ignored.

---

```
from error_tracker.django.middleware import track_exception

@track_exception
```

(continues on next page)

(continued from previous page)

```
def do_something():
    ...
```

## 6.3 Notification notify feature

Notifications are very useful in the case of failure, in different situations notification can be used to notify users using different channels like Slack, Email etc. Notification feature can be enabled by providing a *NotificationMixin* object.

```
from error_tracker import NotificationMixin
class Notifier(NotificationMixin):
    def notify(self, request, exception,
               email_subject=None,
               email_body=None,
               from_email=None,
               recipient_list=None):
        # add logic here
```

### 6.3.1 Flask App Usage

```
error_tracker = AppErrorTracker(app=app, db=db, notifier=Notifier())
```

### 6.3.2 Django App Usage

settings.py

```
APP_ERROR_NOTIFICATION_MODULE = "path to Notifier class"
```

## 6.4 Ticketing

Ticketing interface can be used to create tickets in the systems like Jira, Bugzilla etc, ticketing can be enabled using ticketing interface.

Using TicketingMixin class

implement raise\_ticket method of TicketingMixin interface

```
from error_tracker import TicketingMixin
class Ticketing(TicketingMixin):
    def raise_ticket(self, exception, request=None):
        # Put your logic here
```

### 6.4.1 Flask App Usage

```
app = Flask(__name__)
db = SQLAlchemy(app)
error_tracker = AppErrorTracker(app=app, db=db, ticketing=Ticketing())
db.create_all()
```

## 6.4.2 Django App Usage

settings.py

```
APP_ERROR_TICKETING_MODULE = "path to Ticketing class"
```

## 6.5 Masking Rule

Masking is essential for any system so that sensitive information can't be exposed in plain text form. Flask error monitor provides masking feature, that can be disabled or enabled.

- Disable masking rule: set `APP_ERROR_MASKED_KEY_HAS = ()`
- To set other mask rule add following lines

```
#Mask all the variables or dictionary keys which contains from one of the following_
↳tuple
APP_ERROR_MASKED_KEY_HAS = ( 'secret', 'card', 'credit', 'pass' )
#Replace value with `#####`
APP_ERROR_MASK_WITH = "#####"
```

---

### Note:

- Masking is performed for each variable like dict, list, set and all and it's done based on the *variable name*
- Masking is performed on the dictionary key as well as e.g. *ImmutableMultiDict*, *QueryDict* standard dict or any object whose super class is dict.

---

### Custom masking rule using MaskingMixin

---

**Note:** implement `__call__` method of `MaskingMixin`

---

```
from error_tracker import MaskingMixin
class MyMaskingRule(MaskingMixin):
    def __call__(self, key):
        # Put any logic
        # Do not mask return False, None
        # To mask return True, Value
```

## 6.5.1 Flask App Usage

```
error_tracker = AppErrorTracker(app=app, db=db,
                                masking=MyMaskingRule("#####", ('pass', 'card'))
↳) )
```

## 6.5.2 Django App Usage

settings.py

```
APP_ERROR_MASKING_MODULE="path to MyMaskingRule"
APP_ERROR_MASKED_KEY_HAS = ('pass', 'card')
APP_ERROR_MASKED_WITH = "#####"
```

## 6.6 Custom Context Builder

Having more and more context about failure always help in debugging, by default this app captures HTTP headers, URL parameters, any post data. More data can be included like data-center name, server details and any other, by default these details are not captured. Nonetheless these details can be captured using ContextBuilderMixin. Error Tracker comes with two type of context builders DefaultFlaskContextBuilder and DefaultDjangoContextBuilder for Flask and Django respectively. We can either reuse the same context builder or customize them as per our need.

### Using ContextBuilderMixin

**Note:** Implement get\_context method of ContextBuilderMixin, default context builders capture *request body, headers* and URL parameters.

```
from error_tracker import ContextBuilderMixin
class ContextBuilder(ContextBuilderMixin):
    def get_context(self, request, masking=None):
        # return context dictionary
```

### 6.6.1 Flask App Usage

This custom context builder can be supplied as parameter of AppErrorTracker constructor.

```
error_tracker = AppErrorTracker(app=app, db=db,
                                context_builder=ContextBuilder())
```

### 6.6.2 Django App Usage

Add path of the custom builder class to the settings file, this class should not take any arguments for constructions.

#### settings.py

```
APP_ERROR_CONTEXT_BUILDER_MODULE = "path to ContextBuilder class"
```

## 6.7 Using Mongo or other data store

Using any data store as easy as implementing all the methods from **ModelMixin**

```
from error_tracker import ModelMixin
class CustomModel(ModelMixin):
    objects = {}

    @classmethod
    def delete_entity(cls, rhash):
```

(continues on next page)

(continued from previous page)

```
...

    @classmethod
    def create_or_update_entity(cls, rhash, host, path, method, request_data,
    ↪exception_name, traceback):
        ...

    @classmethod
    def get_exceptions_per_page(cls, page_number=1):
        ...

    @classmethod
    def get_entity(cls, rhash):
        ...
```

### 6.7.1 Flask App Usage

Create app with the specific model

```
error_tracker = AppErrorTracker(app=app, model=CustomModel)
```

### 6.7.2 Django App Usage

Add path to the model in settings file as

```
APP_ERROR_DB_MODEL = core.CustomModel
```